

# COMBI FLEXO SOLVENT

## Specifications

- Simultaneous processing system of the entire sheet surface.
- Pre-exposure and main exposure with pump and vacuum gauge.
- Fixing profile on the table with permanent adhesive plate and automatic tilting.
- Washing out with automatic brush height adjustment via PLC and with an orbital and alternating movement.
- Final cleaning area with one rotating brush.
- Drying area with 2 drawers.
- Post-exposure and finishing with LED control lamps for on/off status of the lamps.
- Separate extraction system for washing/drying area and post-exposure/finishing.
- 9-channel touchscreen controller, for any desired thickness and relief: pre-exp. time, main exposure, wash time, auto regeneration amount, post-treatment, finish time for each of the 2 drawers.
- Automatic Solvent Level Control.
- Solvent and dryer temperature control.

	<b>27/35</b>	<b>30/40</b>	<b>36/47</b>	<b>42/60</b>
<b>Exposure format (mm)</b>	700x900	780x1067	920x1200	1070x1530
<b>Exposure size (inches)</b>	27"x35"	31"x42"	36"x47"	42"x60"
<b>Tank volume (l)</b>	90	90	120	140
<b>UVA exposure lamps</b>	16x60W 10R L.1200	16x60W 10R L.1200	18x80W 10R L.1500	-
<b>UVA post-exposure lamps</b>	14x60W 10R L.1200	14x60W 10R L.1200	17x80W 10R L.1500	28x80W 10R L.1500
<b>UVC lamps</b>	13x36W L.1200	13x36W L.1200	16x60W L.1500	27x60W L.1500
<b>UVC lamps</b>	7	7	7	7
<b>Wattage (kW)</b>	15	15	21	21
<b>Electrical power supply</b>	230V 3F + GND 60Hz 400V 3F + N + GND 50Hz			
<b>Overall dimensions (LxWxH) (cm)</b>	290x180x135	290x180x135	320x215x135	370x241x135