

FLEXO WATER COMBI FLW

Specifications

- Simultaneous processing system of the whole plate surface
- Pre- and main exposure with pump and vacuum gauge
- Fixing part on the table with permanent adhesive plate and automatic reversal. Washing out with automatic height adjustment of brushes and with an orbital and alternating movement. Independent movement of the table
- Final cleaning section with one rotating cylindrical brush
- Drying area with 2 independent drawers
- Post-exposure and finishing area with LEDs that inform the status of the lamps 9-channel touchscreen controller, for any desired thickness and relief: pre-exp. Time, Main Exposure, Wash Out Time, Auto Regeneration Amount, Post Exp. finish, 2 times for each of the 2 drawers
- Temperature control of water and drying section
- Detergent dosing pump
- Sand filter system

	27/35	30/40
Exposure size (mm)	700x900	780x1030
Exposure size (inches)	27"x35"	30"x40"
Amount of developer in tank (l)	110	110
UVA exposure lamps	N.16 60W 10R L.1200	N.16 60W 10R L.1200
UVA lamps after exposure	N.14 60W 10R L.1200	N.14 60W 10R L.1500
UVC lamps	N.13 36W L.1200	N.13 36W L.1200
Maximum thickness workable (mm)	3.94	3.94
Wattage (kW)	15	15
Electrical power supply	230V 3F + GND 60Hz 400V 3F + N + GND 50Hz	
Overall dimensions (LxWxH) (cm)	290x180x135	290x180x135