

# GS LINE

## Specifications

- Washing out and pre-drying area
- touchscreen controller of each work step
- Washing is performed by two orbital brushes
- Removing excess water with a sponge roller
- Adhesive plate for polyester sheets on request
- Filtration section for digital plates with cylindrical brush

### Optional:

- Tunnel dryer with post-exposure sections (length: 163.5 cm)
- Exhibitor under the tunnel

<b>Max plate size (mm)</b>	500	700	900
<b>Max. Plate size (inches)</b>	19.6"	27.5"	35.4"
<b>UVA lamps (with TUNNEL)</b>	4x40W L 600	4x60W L. 1200	4x60W L. 1200
<b>Tank capacity (l)</b>	110 liters	110 liters	110 liters
<b>Wattage (kW) machine</b>	12	14	16
<b>1: Electric power supply machine</b>	230V (3PH + GND) 60Hz 400V (3F + N + GND) 50Hz		
<b>Wattage (KW) Boiler</b>	26 kW	26 kW	26 kW
<b>1: Boiler electrical supply</b>	400V (3PH+GND)		
<b>Wash dryer</b>	2x2000	2x2000	2x2000
<b>Dryer heater (kW)</b>	4	6	6
<b>Overall dimensions (LxWxH) (cm)</b>	110x300x117	130x360x120	140x360x129
<b>Weight (kg)</b>	400	480	700